



Hand in hand

Integrating electrical and automation systems

Peter Tubaas, Martin Stannestro

As process plants get larger and more complex, automation systems must handle an ever-increasing number of signals. At the same time, the number of electrical consumers increases, making an electrical control system essential. The electrical control system is an automation system in itself, providing an interface between the process control and the electrical consumers and actuators. ABB takes responsibility for all these systems and their integration. By letting ABB handle the integration and all the interfaces, customers benefit from faster project execution, reduced re-engineering, higher quality and higher operational efficiency.

Productivity

Electrical systems are clearly a core part of any process plant, providing electrical energy to drive motors, energize heaters and power lighting and auxiliary equipment. The electrical system is invariably complex, relying on thousands of components and kilometers of cabling. The complexity of the system increases with the size of the process plant. Such large process plants are reliant on automation systems to operate efficiently and safely. These automation systems will typically respond to tens of thousands of signals in a quick, predictable and reliable manner. The seamless integration of the electrical and automation systems are highly desirable in a process plant, a benefit recognized by ABB at the StatoilHydro Snøhvit liquefied natural gas (LNG) plant. Here, the electrical control and supervision System (ECSS) communicates with a wide range of equipment and ensures a stable power supply to the LNG facility.

No system is more critical to the processing plant than the combined safety and automation system.

Snøhvit

The Snøhvit field – named after the fairytale character Snow White – was discovered more than 25 years ago. The road to develop this gas field was long and winding, but the project finally went online in October 2007.

The uninhabited island of Melkøya, not far from the town of Hammerfest, has turned into the largest building site in Northern Europe, and the largest construction project that Norway has ever seen.

Gas from the Snøhvit field, approximately 140 kilometers offshore in the Barents Sea, is flowing into the gas processing plant for treatment and shipping to the global LNG market. The core products of the plant are liquefied natural gas (LNG; 5.67 billion m³/year), liquefied petroleum gas (LPG; up to 250,000 tonnes/year) and condensate (up to 900,000 m³/year). All products are exported by ship.

Snøhvit is the first development in the Barents Sea. The oil and gas fields were discovered in the early 1980s. Combined with the adjacent Albatross and Askeladd fields, Snøhvit contains more than 300 billion m³ of natural gas. Gas is extracted from the seabed using subsea equipment, which is operated remotely from Melkøya. The subsea control system was delivered by ABB in the United Kingdom (now Vetco Aibel). The topside of the subsea control system, which is an integrated part of the overall Safety and Automation System (SAS), was delivered by ABB in Norway.

Complete control of the plant

Snøhvit is an extremely complex installation. The process is extensive, encompassing subsea control processing, complex LNG processes, and

storage and loading of the final products.

No system is more critical to the processing plant than the combined safety and automation system. The number of signals running through the Snøhvit process is enormous; the Process Control and Data Acquisition (PCDA) system has to handle more than 30,000 signals simultaneously. An unscheduled halt in production is extremely costly. Therefore, ABB's control systems are constructed and tested to provide the highest level of security and minimal downtime.

The hot exhaust gases from the gas turbines are used to provide heat for the parts of the process that demand high temperatures.

The philosophy of process plant owners in general, and StatoilHydro in particular, is to provide its operators with a “single window” into the plant. ABB's 800xA Extended Automation System provides this facility and was, therefore, chosen for the Snøhvit project.

Plant power demand

Complexes for liquefied natural gas require a reliable and stable energy supply. Most LNG plants are, however, situated in areas in which the

MS Nordlys, one of the ships of Hurtigruten – The Norwegian coastal ship operator – entering the port of Hammerfest



1 Snøhvit is located on the northern coast of Norway.



power supply is either unreliable or nonexistent. The Snøhvit plant is no exception and must, therefore, rely on its own power supply.

To meet the power demand, the Snøhvit plant contains a 1.65 TWh/year power plant with five gas-turbine-driven generators of about 50 MW each. These power the large refrigeration compressors of up to 65 MW, driven by variable-speed electrical motors, which are required to liquefy gases. The hot exhaust gases from the gas turbines are used to provide heat for other parts of the process. This setup saves energy and provides about 10 additional uptime days per year due to the much higher availability of electrical drivers (as compared to gas turbine drivers).

Snøhvit contains more than 300 billion m³ of natural gas. Gas is extracted from the seabed using subsea equipment, which is operated remotely from Melkøya.

The Snøhvit plant not only includes its own power station and large compressor drivers, but also a large distribution network with several thousand relatively small electrical consumers. A large variety of ABB electrical components, products and systems are included in ABB's deliveries to the

plant. These include high-voltage switchgear of the EXK-0 type, rated for 145 kV, and medium-voltage switchgear of the UniGear ZS1 type, rated for 6.6 kV and 11 kV. Also included are optical arc detection systems to provide early detection and quick protective action of switchgear to extinguish arcs. Further, MNS-type switchgear is used at low-voltage levels of 400 V and 690 V. Some 500 cubicles supplying power to about 2,500 consumers are included at these voltage levels; of which some 600 consumers are INSUM starters (intelligent motor starters) and 75 consumers are ACS 800 variable-speed drives. ABB's protection and control unit (REF542) is used throughout the plant to provide the highest level of security and selective protection actions in the event of a fault in the power system.

Electrical control and supervision

The complex nature of the electrical system requires an automated ECSS. This system is required to unite the thousands of motors, switches, contactors and circuit breakers, and to minimize the effects should a fault develop. A single unscheduled shutdown for the entire plant is extremely expensive.

The ECSS is at the heart of the electrical system and communicates with the vast range of ABB products using serial links and Ethernet. It is also linked with the automation system and other third-party deliveries. The system consists of 48 AC800M controllers. The

ECSS processes some 44,000 signals at any one time – more than the plant's automation system. The ECSS provides a wide range of functions, enabling a stable power supply to the plant, lowering operation costs and reducing emissions, while at the same time increasing safety.

The uninhabited island of Melkøya, not far from the town of Hammerfest, has turned into the largest building site in Northern Europe, and the largest construction project that Norway has ever seen.

An important part of the ECSS is the Power Management System (PMS). Since a relatively small fault may lead to a cascade of equipment shutdowns that could affect a large part of or the entire plant, faults must be handled quickly and appropriately to avoid a domino effect. ABB's PMS is also based on the 800xA Extended Automation System and is designed to monitor, control and protect all sections of a process plant. It includes functions such as:

- Supervisory control and data acquisition (SCADA), including generator, circuit breaker, mode and motor control
- Power control, including tie-line control, peak shaving and load sharing

An ABB engineer taking an overview of the plant at Melkøya (Photo: Peter Tubaas, ABB)



Two ABB engineers discussing the plans for the day at the LNG plant in Melkøya (Photo: Peter Tubaas, ABB)



Productivity



- Load shedding, including fast, slow and frequency-based load shedding, as well as manual load shedding

Probably one of the most important and most frequently relied upon parts of the PMS is the load-shedding function, which helps ensure that the consequences of any one fault in the electrical system have the smallest possible impact on the functioning of the plant. ABB has delivered and commissioned more than 30 PMSs worldwide, demonstrating that the PMS substantially improves plant uptime, efficiency and reliability.

ABB can draw on more than 50 years of experience with automation and electrical systems to optimize their integration.

The ECSS not only provides an interface between the process plant's automation and electrical systems; it also provides indispensable functionality and reliability in a plant where a system shutdown could cost millions of dollars. Although full communication and data exchange with the process plant's automation system is provided, the ECSS does not depend on it to operate. On the contrary, the ECSS can operate in isolation to ensure safe and reliable operation of the electrical system.

Main electrical vendor approach

In the past, oil companies and engineering, procurement and construction (EPC) contractors have very often purchased different types of equipment (eg, transformers, high-voltage switchgear, medium-voltage switchgear and low-voltage switchgear) under separate contracts. Project risks can be reduced, however, by including most of the electrical equipment and systems – as well as engineering – under one large contract. The result is lower costs and faster project execution with safer systems that are fully integrated and interoperable. Safety is improved during installation and commissioning since project coordination is more easily achieved with only one contractor.

StatoilHydro recognized the merit of such an approach and merged all purchases of high-voltage, medium-voltage and low-voltage switchgear, as well as the ECSS, for the Snøhvit project into a single contract. In addition to equipment delivery, ABB provided a wide range of engineering services, including a long list of electric network studies. These are required to ensure safe operation and maximum efficiency of the plant.

Since the Snøhvit plant is physically connected to the northern Norwegian power grid, it soon became of interest to study the dynamic behavior of the entire plant – including the gas turbine generator sets – and its connection to

the grid. ABB has performed a dynamic stability study that was used to set and adjust the parameters of the power management system, as well as the dedicated generator control algorithms. This ensures not only stable operation of the process plant, but also ensures that the process plant contributes to the stability of the northern Norwegian power grid – as required by the grid operator.

Complexes for liquefied natural gas require a reliable and stable energy supply. Most LNG plants are, however, situated in areas in which the power supply is either unreliable or nonexistent.

ABB at the cutting edge

ABB can draw on more than 50 years of experience with automation and electrical systems to optimize their integration. Uniting the electrical and automation systems is becoming a necessary feature of large process plants. Operating such plants without an automated system is almost unthinkable, not only for safety reasons, but also for reasons of cost savings and increased efficiency. Customers such as StatoilHydro rely on experienced companies like ABB to ensure safe and reliable plant operations.

Peter Tubaas

ABB Corporate Communications
Billingstad, Norway
peter.tubaas@no.abb.com

Martin Stannestro

ABB Process Automation
Oslo, Norway
martin.stannestro@no.abb.com